Applicant: Roberto Polidoro et al. Attorney's Docket No.: 08774-275US1 / MEG0884

Serial No.:

Filed : June 17, 2005

Page : 2 of 6

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

<u>Listing of Claims</u>:

1-23. (Canceled)

24. (New) A method of conveying a banknote comprising:

frictionally engaging at least three points with the banknote so as to partially deform the banknote, two of the points engaging opposite faces of the banknote; and

moving at least one of the points in a direction of intended movement of the banknote so that, at least during conveyance of the banknote, the points have a fixed relative spacing for any given position of the points and for any given banknote and wherein the at least one point moves to convey the banknote against a reference surface orientated in a direction of movement of the banknote so that the banknote rotates to align the banknote.

- 25. (New) A method according to claim 24 wherein the points are arranged in a line.
- 26. (New) A method according to claim 24 including moving the banknote relative to at least one point while moving the at least one point.
- 27. (New) A method according to claim 24 including inhibiting movement of the banknote if a force required to move the banknote exceeds a predetermined limit.
 - 28. (New) A banknote conveyor comprising:

at least two surfaces which frictionally engage opposite sides of a banknote so as to deform the banknote and which move to transport the banknote,

Applicant: Roberto Polidoro et al. Attorney's Docket No.: 08774-275US1 / MEG0884

Serial No. :

Filed : June 17, 2005

Page : 3 of 6

said surfaces being arranged so that, at least during transport of the banknote, the surfaces have a fixed relative spacing for any given position of the surfaces and for any given banknote,

said conveyor further including a reference surface against which the banknote is conveyed.

- 29. (New) A banknote conveyor according to claim 28 wherein said surfaces define at least three points of engagement with the banknote.
- 30. (New) A banknote conveyor according to claim 29 wherein the banknote moves relative to at least one point while being conveyed.
- 31. (New) A banknote conveyor according to claim 28 which includes a first and a second corrugated roller.
- 32. (New) A banknote conveyor according to claim 31 wherein the first and the second rollers are engageable to create a seal.
- 33. (New) A banknote conveyor according to claim 28 which includes a first and a second cam.
 - 34. (New) A banknote conveyor according to claim 28 which includes three rollers.
- 35. (New) A banknote conveyor according to claim 28 comprising means for limiting movement of the conveyor if a force required to move the banknote exceeds a predetermined limit.
 - 36. (New) A banknote conveyor comprising at least two surfaces moveable between a

Applicant: Roberto Polidoro et al. Attorney's Docket No.: 08774-275US1 / MEG0884

Serial No.:

Filed : June 17, 2005

Page : 4 of 6

first position and a second position so that in the first position the surfaces define an undulate banknote path and in the second position the surfaces engage to provide a seal.

37. (New) A banknote conveyor according to claim 36 wherein said surfaces define at least a portion of a banknote entryway.

- 38. (New) A banknote changer comprising banknote uptake means and banknote alignment means, the uptake and alignment means each further comprising a banknote conveyor according to claim 28.
- 39. (New) A banknote conveyor which engages a banknote by means of surfaces which define a gap of predetermined configuration which is wider than the thickness of the banknote and of non-linear configuration so as to cause bending of the banknote when viewed in the direction of transport so that the force by which the banknote is gripped is dependent upon the rigidity of the banknote and which acts to align the banknote by conveying the banknote against a reference surface orientated in a direction of travel of the banknote so that the banknote rotates.
- 40. (New) A banknote conveyor comprising at least two complementary surfaces which at least partially engage the banknote and move to convey the banknote, at least one of said surfaces including blocking means to prevent insertion of objects into the conveyor when said surfaces are stationary.
- 41. (New) A banknote conveyor according to claim 40 wherein the blocking means includes notches formed on at least one of the complementary surfaces.
- 42. (New) A banknote conveyor according to claim 40 which includes means for inhibiting the movement of said surfaces when the conveyor is not in use.

Attorney's Docket No.: 08774-275US1 / MEG0884 Applicant: Roberto Polidoro et al.

Serial No.:

Filed : June 17, 2005 Page : 5 of 6

43. (New) A method of conveying a banknote comprising: conveying the banknote with a force dependent on a rigidity of the banknote, and inhibiting movement of the banknote if the force exceeds a predetermined limit.

- (New) A method according to claim 43 wherein a torque limiter is used to inhibit 44. movement of the banknote.
- (New) A method according to claim 43 wherein a clutch is used to inhibit 45. movement of the banknote.